In Accordance with Directive 2001/58/CE

1. Chemical Product

MSDS Name: Alkaline Battery

Model: LR03 & LR6 & LR14 & LR20 & LR8D425 & 6LR61

Manufacturer: SICHUAN CHANGHONG NEWENERGY TECHNOLOGY CO., LTD.

Address: No.35, East Mianxing Road, High-Tech Park, 621000, Mianyang, Sichuan, China

Tel / Fax: +86-816-2415060

## 2. Composition /Information on Ingredients:

Chemical Nature: Chemical power source

CAS-No/EINECS NO.: Not applicable.

INCI CTFA-Description: Alkaline Zinc-Manganese Dry Battery

Tariff No.: "W" 850610 1210

IMPORTANT NOTE: The battery shall not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

MATERIAL OR INGREDIENT	CAS#	PEL (OSHA)	TLV (ACGIH)	% (by Wt.)
Graphite	7782-42-5	15 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> TWA (respirable fraction)	2 mg/m <sup>3</sup> TWA (respirable fraction)	2~6
Manganese Dioxide	1313-13-9	5 mg/m³ Ceiling (as Mn)	0.2 mg/m <sup>3</sup> TWA (as Mn)	30~45
Potassium Hydroxide	1310-58-3	None established	2 mg/m³ Ceiling	4~8
Zinc	7440-66-6	15 mg/m <sup>3</sup> TWA PNOR* (total dust) 5 mg/m <sup>3</sup> TWA PNOR* (respirable fraction)	10 mg/m³ TWA PNOC** (inhalable particulate) 3 mg/m³ TWA PNOC** (respirable particulate)	12~25

<sup>\*</sup> PNOR: Particulates not otherwise regulated

Date: 01/01/2023

MATERIAL OR	CAS#	Directive 2006/66/EC Limit	PPM (by Wt.)	
INGREDIENT	CAS#	(PPM)		
Mercury	7439-97-6	5	Not detected (≤ 1ppm)	
Cadmium	7439-92-1	20	Not detected (< 5ppm)	
Lead	7440-43-9	40	Not detected (< 20ppm)	

#### 3. Hazards identifications

General: Alkaline battery --- The Common known rules for handing of chemical power

source should be obeyed. Do not heat, recharge, disassemble the product or

dispose of in fire.

Physical-Chemical Hazards: The chemical materials concluded in the Product is sealed up, thus being

stable, safe and eco-friendly under common conditions, may not cause

SICHUAN CHANGHONG NEWENERGY TECHNOLOGY CO., LTD.

<sup>\*\*</sup> PNOC: Particulates not otherwise classified

#### In Accordance with Directive 2001/58/CE

physical-chemical hazards.

Disassemble the product without a professional basis, may cause leakage of Hazards to Human being:

the electrolyte and irritation to skin.

Dispose the product without separate collection, may lead to pollution Hazards to environment:

caused by Hg/Cd/Pb (micro trace), or by the electrolyte of alkaline

Date: 01/01/2023

solution.

### 4. First-aid measures

Inhalation: Not applicable.

Skin Contact: Wash with clean water immediately once leakage happens and the inner liquid splashes onto

Eye contact: Rinse eyes immediately with running water for at least ten minutes. Consult an

ophthalmologist.

Ingestion: Rinse mouth with water; Give plenty of water to drink. Obtain medical advice.

## 5. Fire-fighting measures

Suitable extinguishing media: Carbon dioxide (CO<sub>2</sub>), foam, dry chemical powder. Extinguishing media not to be used: Never use a direct water jet, may pollute the water

system.

Exposure hazards from combustion products: In case of fire, carbon monoxide or other toxic

organic substances may be generated. Do not inhale fumes and smoke.

Wear full protective clothing. Use self contained Personal protective equipments:

breathing apparatus.

\* Remark: It can be extinguished by car extinguisher as well.

#### 6. Accidental release measures

Personal precautions: Wear protective clothing. Keep unprotected persons away.

Environmental precautions: Avoid discharge and penetration into sewerage systems, waterways, pits, and

cellars.

Methods for cleaning up: Collect spilled material with an insert standard absorbent like sand or silica.

Care for well-Ventilated conditions. Recycle or dispose of the materials in an

appropriate way.

#### 7. Handling and storage

General: Obey the common known rules and precautions for handling with chemical

power sources.

Fire/Explosion protections: Explosion may happen if short-circuit; collect spilled material with an insert

standard absorbent like sand or silica.

Store product in clean, cool and ventilated place with a temperature between Storage:

 $10^{\circ}$ C and  $30^{\circ}$ C (no higher than  $40^{\circ}$ C in the ordinary course of events) and a relative humidity no higher than 65%; the storage time should not be too long;

Page 2 of 4

In Accordance with Directive 2001/58/CE

the batteries should be well-arranged, and do avoid soft-circuit caused by the contact of the positive and negative electrodes.

Date: 01/01/2023

## 8. Exposure controls/Personal protection

Exposition/ Technical measures: Not applicable.

Protection of hands, eyes and skin: To protect hands, eyes and skin, do not disassemble the

product without professional basis.

### 9. Physical and chemical propertied

Physical state	Solid	Solubility in water	not applicable
Color	not applicable	Vapor pressure	not applicable
Odor	not applicable	Explosion limit	not applicable
pH value	not applicable	Oxidizing properties	not applicable
Specific gravity	not applicable	Flashpoint	not applicable
Refractive index	not applicable	Auto flammability	not applicable
Solubility in ethanol	not applicable	Partition coefficient	not applicable
Melting Point	not applicable	<b>Boiling Point</b>	not applicable
Freezing Point	not applicable		

## 10. Stability and Reactivity

The chemical materials concluded in the Product are sealed up, thus being stable, safe and eco-friendly under common conditions.

#### 11. Toxicological information

The product is multi component mixture for which no toxicological data exists.

Precautions avoid disassembling the product without a professional basis.

#### 12. Ecological information

In general, no ecological data is available for preparations.

Precautions avoid disposing into drainage systems and into the environment.

### 13. Disposable considerations

Precautions avoid disposing waste products into environment, sewerage, landfills or by incineration. Obey the rules and precautions for separate collection and recycling of the waste products.

#### 14. Transport Information

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for our alkaline battery product has been designed to be compliant with these regulatory concerns.

Alkaline batteries (sometimes referred to as "Dry battery" or "Dry cell" batteries) are not listed as dangerous goods under the ADR European Agreement Concerning the International Carriage of Dangerous Goods by Road, the IMDG International Maritime Dangerous Goods Code,

#### In Accordance with Directive 2001/58/CE

NEWENERGY Date: 01/01/2023

UN Dangerous Good Regulations, IATA Dangerous Goods Regulations (IATA DGR) (64th) Technical Industrial and the U.S hazardous materials regulations (49 CFR).

The batteries are not subject to the dangerous goods regulations provided they meet the requirements contained in the following special provisions: 510703502192

Regulatory Body	Special Provisions	
ADR	Not regulated	
IMDG	Not regulated	
2UN	Not regulated	
US DOT	49 CFR 172.102 Provision 130	
IATA	A123 (not regulated)	
ICAO	Not regulated	

All our alkaline battery products are packed in such a way to prevent short circuits or the generation dangerous quantities of heat and meet the special provision listed above. In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instruction require the words "not restricted" and the Special Provision number A123 be provided on the air waybill, when an air waybill is issued.

## 15. Regulatory Information

**Symbol:** for transportation, collection, or environment protection (stipulated respectively

by each contract).

Contains: transportation marks;

"separate collection" symbol; "RoHS" symbol (maybe), etc.

### 16. Other information

The information on this Material Safety Date Sheet (MSDS) was obtained from current and reputable sources. For any other question, please contact the manufacturer for further information.

SICHUAN CHANGHONG NEWENERGY TECHNOLOGY CO., LTD. Tel / Fax: +86-816-2415060