Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: FHS-International GmbH&Co.KG						
Supplier's addres	s: An der Eickesmü	hle 34, D 41238 Mönc	hengladbach			
Model identifier:	14445T					
Type of light sour	ce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type (or other electric interface)		Connectors				
Mains or non-mains:		NMLS	Connected light source (CLS):			
Colour-tuneable light source:			Envelope:			
High luminance light source:						
Anti-glare shield:			Dimmable:			
		Product para				
Parameter		Value	Parameter	Value		
		General product p	1			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		4,0	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		274 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that	2800K Single value		
On-mode power (P _{on}), ex- pressed in W		3,2	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second dec- imal		_	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	64		
Outer dimen-	Height	550	Spectral power dis-			
sions without separate con- trol gear, light- ing control parts and non- lighting con- trol parts, if any (millime- tre)	Width Depth	1 6000	tribution in the range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a) Parameters for LED and OLED light sou			If yes, equivalent power (W)			
			Chromaticity coordi- nates (x and y)	0.4719 0.4420		
Parameters for LED R9 colour rendering		rces:	Survival factor	0,9		
no coloui renuering	, much value	1	Jul vival lactUI	0,5		

the lumen maintenance factor	94,80%					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)		Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated bal-last of a particular wattage.		If yes then replace- ment claim (W)				
Flicker metric (Pst LM)		Stroboscopic effect metric (SVM)				

(a)₁-¹: not applicable; (b)₁-¹: not applicable;