Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Nedis

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

Model identifier: WIFILX01W50


Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	N/A		
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
Product parameters			
Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	2	Energy efficiency class	G
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	120 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500
On-mode power (P_{on}), expressed in W	1,8	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	69
Outer dimensions without separate control gear, lighting control — Height	30	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
Width	5		
Depth	5 000		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[(a)]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,486 0,432
Parameters for LED and OLED light sources:				
R9 colour rendering index value		-15	Survival factor	0,90
the lumen maintenance factor		0,90		

[(a)] '-' : not applicable;

[(b)] '-' : not applicable;


1.0
0.8
0.6
0.4
0.2
0
350
425
500
575
650
725
800