## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

<b>Supplier's name or trade mark:</b> Nedis	,
---	---

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

Model identifier: WIFILX01W200

_	•			
Ivpe	Ot	light	source:	

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	N/A			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes	
Colour-tuneable light source:	No	Envelope:	<del>-</del>	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
Product parameters				

Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
<u> </u>	mption in on- 00 h), rounded st integer	2	Energy efficiency class	G
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	145 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	2,3	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,50
(P <sub>net</sub> ) for CLS, 6	andby power expressed in W the second dec-	0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	69
Outer dimen-	Height	30	Spectral power dis-	See image
sions without	Width	5	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	20 000	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,485
		nates (x and y)	0,430
Parameters for LED and OLED light sources:			
R9 colour rendering index value	-14	Survival factor	0,90
the lumen maintenance factor	0,90		

(a)'-': not applicable; (b)'-': not applicable;

