Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	Wiz

Supplier's address:	WiZ, WiZ I.B.R.S.	/ C.C.R.I. Number 10461	, 5600VB Eindhoven, NL
---------------------	-------------------	-------------------------	------------------------

Model identifier: 9)290030176W
---------------------	-------------

_	•			
Type	Λt	liaht	COLL	rca.
IVDE	VI.	HEIIL	SOUI	LC.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Product parameters					
Parameter		Value	Parameter	Value	
	General product parameters:				
	mption in on- 00 h), rounded st integer	5	Energy efficiency class	F	
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500	
On-mode pressed in W	oower (P _{on}),	4,9	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90	
Outer	Height	113	Spectral power	See image	
dimensions	Width	35	distribution in the	in last page	

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	35	range 250 nm to 800 nm, at full-load	
Claim of equiva	lent power ^(a)	Yes	If yes, equivalent power (W)	50
			Chromaticity	0,312
			coordinates (x and y)	0,328
Parameters for	LED and OLED lig	ht sources:		
R9 colour rende	ring index value	0	Survival factor	0,90
the lumen maintenance factor		0,93		
Parameters for LED and OLED mains light sources:				
displacement fa	ctor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
source replaces	an LED light s a fluorescent hout integrated icular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)'-': not applicable; (b)'-': not applicable;

