## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: tomons

Supplier's address: F&M Technology GmbH, Fraunhoferstraße 7, 04178 Leipzig, DE

## Model identifier: LP03001

## Type of light source:

High luminance light source: Anti-glare shield:	No No	Dimmable:	Yes
Colour-tuneable light source:	No	Envelope:	-
		source (CLS):	NU
(or other electric interface) Mains or non-mains:	MLS	Connected light	No
Light source cap-type	E27		
Lighting technology used:	LED	Non-directional or directional:	NDLS

Parameter		Value	Parameter	Value		
General product parameters:						
0,	nption in on- 100 h), rounded st integer	8	Energy efficiency class	F		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode p expressed in W	oower (P <sub>on</sub> ),	8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
for CLS, expres	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer dimensions without	Height	60	Spectral power	See image		
	Width	60	distribution in the	in last page		
	Depth	110	1	Page 1 /		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	lf yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,441 0,404			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	60	Survival factor	1,00			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	3			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1			

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

