Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | | | | | | | | |
|--|--------|------------------------|--|--------------|--|--|--|--|
| Supplier's name or trade mark: LED line® | | | | | | | | |
| Supplier's address: Product Menager, Dębowa 1 07-410 Tobolice Mazowieckie Rzekuń Polska | | | | | | | | |
| Model identifier: 243400 | | | | | | | | |
| Type of light source: | | | | | | | | |
| Lighting technology used: | | LED | Non-directional or directional: | NDLS | | | | |
| Light source cap-type | | 12VDC | | | | | | |
| (or other electric interface) | | | | | | | | |
| Mains or non-mains: | | NMLS | Connected light source (CLS): | No | | | | |
| Colour-tuneable light source: | | No | Envelope: | - | | | | |
| High luminance light source: | | No | | | | | | |
| Anti-glare shield: | | No | Dimmable: | No | | | | |
| Product parameters | | | | | | | | |
| Parameter | | Value | Parameter | Value | | | | |
| General product parameters: Energy consumption in on- 1 Energy efficiency F | | | | | | | | |
| mode (kWh/1000 h), rounded up to the nearest integer | | 1 | Energy efficiency class | F | | | | |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 95 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 500 | | | | |
| On-mode power (P _{on}), expressed in W | | 1,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 | | | | |
| Outer | Height | 36 | Spectral power | See image | | | | |
| dimensions without | Width | 21 | distribution in the | in last page | | | | |
| without | Depth | 10 | | | | | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | | range 250 nm to 800 nm, at full-load | | | |
|--|--|------|---|-------|--|--|
| Claim of equivalent power ^(a) | | - | If yes, equivalent power (W) | - | | |
| | | | Chromaticity coordinates (x and y) | 0,314 | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | | 20 | Survival factor | 0,90 | | |
| the lumen maintenance factor | | 0,96 | | | | |

(a)'-': not applicable; (b)'-': not applicable;

