## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLOAILD KLOOL	-A11014 (L0) 2013/2	015 with regard to ener	gy labelling of light
Supplier's name	or trade mark:	LED line®		
Supplier's addre	ss: Product Mer	nager, Dębowa 1 07-	-410 Tobolice Mazowiec	kie Rzekuń Polska
Model identifier	: 247927			
Type of light sou	irce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		<b>G</b> 9		
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para		
Parameter		Value	Parameter	Value
		General product p		I
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		8	Energy efficiency class	F
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		750 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000
On-mode power (P <sub>on</sub> ), expressed in W		8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	19	Spectral power	See image
dimensions	Width	19	distribution in the	in last page
without	Depth	64		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,322			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	9	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	6,1			

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;

